




<b>PRODUCT MATERIAL</b>	Die-cast aluminium
<b>LIGHT SOURCE</b>	Bridgelux V8 Array
<b>MODULE LIFETIME</b>	Approx. 35.000 hours
<b>DRIVER</b>	Including phase cut dimmable driver
<b>COLORS</b>	<ul style="list-style-type: none"> <li>○ 3 = RAL 9003 white</li> <li>● 5 = RAL 9005 black</li> </ul>
<b>BEAM ANGLE</b>	 33°
<b>ADJUSTABLE</b>	No
<b>SIZE</b>	85 X 85 X 93mm




**OPTIONS**

<b>DRIVER OPTIONS</b>	<b>1/10V</b>	500mA 7-10W Art. no.: 0110.500.30.2
	<b>DALI</b>	500mA 7-10W Art. no.: 0110.500.40.2

**INFORMATION**

Full warranty only applies when fixture is purchased in combination with recommended driver.

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources.




**INSERTS**



Black/White



Black



Black/Gold

ARTICLE NUMBER	COLOR	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
5105.994.33.3	○ white	V8 Array	Bridgelux	745lm	9,2W	80lm/W	2700K	>90	35.000 Hrs	500mA
5105.994.33.35	○● white / black	V8 Array	Bridgelux	745lm	9,2W	80lm/W	2700K	>90	35.000 Hrs	500mA
5105.994.33.39	○● white / gold	V8 Array	Bridgelux	745lm	9,2W	80lm/W	2700K	>90	35.000 Hrs	500mA
5105.994.33.5	● black	V8 Array	Bridgelux	745lm	9,2W	80lm/W	2700K	>90	35.000 Hrs	500mA
5105.994.33.53	○● black / white	V8 Array	Bridgelux	745lm	9,2W	80lm/W	2700K	>90	35.000 Hrs	500mA
5105.994.33.59	○● black / gold	V8 Array	Bridgelux	745lm	9,2W	80lm/W	2700K	>90	35.000 Hrs	500mA