

FLAT LINE



PRODUCT MATERIAL	Polycarbonate
ADAPTER	3-phase track adapter
LIGHT SOURCE	Edison 2835 LED
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including in-track driver
COLORS	○ 3 = RAL 9003 white
BEAM ANGLE	Different see options
SIZE	See technical drawing

OPTIONS

DIMMABLE	DALI dimmable
DIFFUSER	Diffuser UGR<19 Opal diffuser On request

INFORMATION

Also available in 1200mm € 130,00




Output current adjustable: Dip switch

Adjustable lumen, wattage and milliampere:


9.760lm	61W	360mA
8.640lm	54W	315mA
7.360lm	46W	270mA
6.080lm	38W	225mA
5.600lm	35W	200mA
4.800lm	30W	175mA
4.000lm	25W	145mA
3.200lm	20W	110mA

Before use, always check dip switch setting

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources.



UGR<19 Diffuser



Dip switch

ARTICLE NUMBER	DESCRIPTION	LUMEN	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	LENGTH	BEAM ANGLE	TC LIFETIME
3280.300.30.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	3000K	>80	1500mm	30°	50.000 Hrs
3280.300.60.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	3000K	>80	1500mm	60°	50.000 Hrs
3280.300.90.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	3000K	>80	1500mm	90°	50.000 Hrs
3280.300.12.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	3000K	>80	1500mm	120°	50.000 Hrs
3280.300.25.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	3000K	>80	1500mm	25° Asymetric	50.000 Hrs
3280.300.66.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	3000K	>80	1500mm	DA60°	50.000 Hrs
3280.400.30.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	4000K	>80	1500mm	30°	50.000 Hrs
3280.400.60.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	4000K	>80	1500mm	60°	50.000 Hrs
3280.400.90.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	4000K	>80	1500mm	90°	50.000 Hrs
3280.400.12.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	4000K	>80	1500mm	120°	50.000 Hrs
3280.400.25.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	4000K	>80	1500mm	25° Asymetric	50.000 Hrs
3280.400.66.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	4000K	>80	1500mm	DA60°	50.000 Hrs
3280.600.30.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	6000K	>80	1500mm	30°	50.000 Hrs
3280.600.60.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	6000K	>80	1500mm	60°	50.000 Hrs
3280.600.90.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	6000K	>80	1500mm	90°	50.000 Hrs
3280.600.12.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	6000K	>80	1500mm	120°	50.000 Hrs
3280.600.25.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	6000K	>80	1500mm	25° Asymetric	50.000 Hrs
3280.600.66.Δ	In Track	3200 - 9760	20 - 61W	160lm/W	6000K	>80	1500mm	DA60°	50.000 Hrs