

PRODUCT MATERIAL LIGHT SOURCE MODULE LIFETIME DRIVER COLORS BEAM ANGLE SIZE

Bridgelux V13B Approx. 50.000 hours Option 8 = Stainless steel

Aluminium body

Ø123 X 158mm

## OPTIONS

OPTIONAL BEAM ANGLE	Art. no.: 8109.000.15.0							
	24• Art. no.: 8109.000.24.0							
DIMMABLE	On request For centralized drivers please contact sales							

## INFORMATION

Tempered glass standard


Including 1,5m cable

Stainless steel ring (316)



For mounting instructions please visit www.key-light.nl. Full warranty only applies when fixture is mounted according to these instructions.





8109.500.55.8 V13B Bridgelux 2500lm 18W 139lm/W 2700K >80 50.000 Hrs Included		ARTICLE NUMBER	LAMP	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA	Driver
8109.000.55.8 V/13B Bridgelux 2500lm 18W 130lm/W 2700K >80 50.000 Hrs 500mA Evoluded		8109.500.55.8	V13B	Bridgelux	2500lm	18W	139lm/W	2700K	>80	50.000 Hrs		Included
bios.oo.ss. Visb bidgelax 2500iii 10VV 105iii/VV 2700K >00 50.000 His 500iiA Excluded		8109.000.55.8	V13B	Bridgelux	2500lm	18W	139lm/W	2700K	>80	50.000 Hrs	500mA	Excluded

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.

## FLOOR 25

