



PRODUCT MATERIAL	Aluminium and PC
LIGHT SOURCE	LED GU10
MODULE LIFETIME	Approx. 30.000 / 50.000 hours
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
BEAM ANGLE	▲ 20° ▲ 36°
BEAM ANGLE (DTW)	▲ 30°
SIZE	Ø60 X 72 X 220mm




OPTIONS

ANTI-GLARE RING	Gold Art. no.: 2 X 3056.922.99.9
------------------------	-------------------------------------

INFORMATION


! Max. hole size for the wall mounting is 40 x 75mm (W X H)

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



Technical drawing

ANTI-GLARE RING



Black

Gold

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	BEAM ANGLE
Δ See colors									
6182.272.20.Δ	GU10	Philips	265lm	2 X 4W	66lm/W	2700K	>90	50.000 Hrs	20°
6182.279.36.Δ	GU10	Philips	265lm	2 X 4W	66lm/W	2700K	>90	50.000 Hrs	36°
6182.282.20.Δ	GU10	Philips	280lm	2 X 4W	70lm/W	3000K	>90	50.000 Hrs	20°
6182.290.36.Δ	GU10	Philips	280lm	2 X 4W	70lm/W	3000K	>90	50.000 Hrs	36°
6182.176.30.Δ	GU10	KL	305lm	2 X 5W	61lm/W	2000 - 3000K	DTW >90	30.000 Hrs	30°