

PRODUCT MATERIAL	Aluminium and Polycarbonate
LIGHT SOURCE	LEDD
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including on/off driver
COLORS	○ 3 = RAL 9010 white
ADJUSTABLE	No
SIZE	595 X 595 X 55mm





OPTIONS

SURFACE FRAME 60 X 60mm	Art. no.: 4743.000.00.3
PENDANT KIT 1000mm	Art. no.: 4743.919.99.1
DIMMABLE	DALI On request
POWER CABLE OPTIONS Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0 Wieland GST18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0 Wieland T connector GST18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0

INFORMATION

High quality PMMA diffuser has excellent durability and is more resistant to UV light discolouration



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	LENGTH	TC LIFETIME	mA
4743.400.40.3	Ledline	LEDD	4000lm	40W	100lm/W	4000K	>80	595 X 595mm	50.000 Hrs	1050mA

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.