



<b>PRODUCT MATERIAL</b>	Di-cast aluminium
<b>LIGHT SOURCE</b>	Philips SLM G7
<b>MODULE LIFETIME</b>	Approx. 50.000 hours
<b>DRIVER</b>	Including Philips Xitanium driver
<b>COLORS</b>	● 7 = RAL 9007 Anthracite
<b>BEAM ANGLE</b>	24°
<b>ADJUSTABLE</b>	Yes
<b>SIZE</b>	Ø163 X 114mm



**OPTIONS**

<b>EMERGENCY MODULE</b>	Art. no.: 0187.003.03.0 - 3 hour						
<b>DIMMABLE</b>	DALI dimmable driver						
<b>POWER CABLE OPTIONS</b> Connected to driver/fixture	<table border="1"> <tr> <td>Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0</td> <td>Included</td> </tr> <tr> <td>Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0</td> <td></td> </tr> <tr> <td>Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0</td> <td></td> </tr> </table>	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0	Included	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0		Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0	
Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0	Included						
Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0							
Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0							

**INFORMATION**



Nominal lifetime L90/B50 @50.000 h - 25°C

Also available in indoor IP40

This luminaire is equipped with an innovative lens technology instead of a reflector  
**High quality led lens technology + 10% more light output**

UGR <19

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



This luminaire is also available in 1100lm SLM on request

**AVAILABLE SLM OPTIONS**

To order the correct product, please replace **COB\*** in the article number field with the COB code found on the last page of the catalogue

ARTICLE NUMBER	LUMINOUS FLUX	BRAND	COLOR TEMPERATURE	SETTING
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	827 / 927 / 830 / 930 / 835 / 840 / 850	High Efficiency
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	Premium White 830 / 930 / 935 / 940	High Efficiency
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	Premium White HE 930	High Efficiency
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	Premium Color 930	High Efficiency
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	Premium Color HE 930	High Efficiency
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	Crisp White 930	High Efficiency
4083. <b>COB*</b> .24.7	2000lm	Philips SLM G7	Food: Meat / Bakery / Iced Seafood / Live Seafood / Vegetables & Fruit	High Efficiency
4083. <b>COB*</b> .24.7	3000lm	Philips SLM G7	827 / 927 / 830 / 930 / 835 / 840 / 850 / 857	High Efficiency
4083. <b>COB*</b> .24.7	3000lm	Philips SLM G7	Premium White 830 / 930 / 935 / 940	High Efficiency
4083. <b>COB*</b> .24.7	3000lm	Philips SLM G7	Premium White HE 930	High Efficiency
4083. <b>COB*</b> .24.7	3000lm	Philips SLM G7	Premium Color 930	High Efficiency
4083. <b>COB*</b> .24.7	3000lm	Philips SLM G7	Premium Color HE 930	High Efficiency
4083. <b>COB*</b> .24.7	4500lm	Philips SLM G7	840 / 850 / 857	High Efficiency

High efficiency is the standard Keylight setting for all SLM G7 LED modules. For COB led specification and warranty information regarding high efficiency, see last page of the catalogue. Standard system warranty is 5 years.