



METEOR 30

PRODUCT MATERIAL	Aluminium and poly-carbonate
LIGHT SOURCE	SMD LED
MODULE LIFETIME	Approx. 40.000 hours
DRIVER	Including on/off driver
COLORS	○ 3 = RAL 9003 white
BEAM ANGLE	△ 120° Wide beam
REFLECTOR PLATE	Opal poly-carbonate diffuser
ADJUSTABLE	No
SIZE	Ø300 X 48mm

OPTIONS

EMERGENCY MODULE	Emergency time: 3 hours
SENSOR	Daylight and microwave sensor:
	Detection area: 140° with 5-7 m distance can be reduced by DIPswitches 25%/50%/75%/100%
	Hold time: 10min/3min/60S/20S
	Daylight sensor: 5Lux/10Lux/50Lux/Disable

INFORMATION

IP 54: For indoor use only


Motion and daylight sensor (MDS) and emergency and sensor (ME) is IP40, others IP54

MDS = Motion and daylight sensor IP40

EM = Emergency module

ME = Emergency and sensor IP40

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME
5142.300.18.3	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	40.000 Hrs
5143.300.18.3MDS	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	40.000 Hrs
5142.300.18.3EM	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	40.000 Hrs
5143.300.18.3ME	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	40.000 Hrs