


PRODUCT MATERIAL	Aluminium and poly-carbonate
LIGHT SOURCE	SMD LED
MODULE LIFETIME	Approx. 40.000 hours
DRIVER	Including driver
COLORS	○ 3 = RAL 9003 white
BEAM ANGLE	
REFLECTOR PLATE	Opal poly-carbonate diffuser
ADJUSTABLE	No
SIZE	Ø300 X 48mm



OPTIONS


EMERGENCY MODULE	Emergency time: 3 hours
SENSOR	Daylight and microwave sensor

INFORMATION

Motion and daylight sensor (SR) and emergency and sensor (EM+SR) is IP40, others IP54

- SR = Motion and daylight sensor IP40
- EM = Emergency module IP54
- EM+SR = Emergency and sensor IP40

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	IP	TC LIFETIME
5142.300.18.3	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	IP54	40.000 Hrs
5143.300.18.3SR	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	IP40	40.000 Hrs
5142.300.18.3EM	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	IP54	40.000 Hrs
5143.300.18.3EM+SR	SMD LED	Epistar	1810lm	18W	100lm/W	3000K	>80	IP40	40.000 Hrs