





PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Citizen CLU701
MODULE LIFETIME	Approx. 35.000 hours
DRIVER	Excluding driver, SELECT OPTION
COLORS (Δ)	<input type="radio"/> 3 = RAL 9003 white <input checked="" type="radio"/> 5 = RAL 9005 black
BEAM ANGLE	 30°
ADJUSTABLE	No
SIZE	Ø64 X 95mm




OPTIONS

OPTIONAL BEAM ANGLE	 38° Art. no.: 4941.010.38.0
DRIVER OPTIONS	On/off 250mA 7-13W Art. no.: 0115.250.10.0 Size: 100 x 43 x 22,5mm
	Phase cut 250mA 7-10W Art. no.: 0110.250.20.4 Size: 100 x 50 x 19mm
	1/10V 260mA 1-14W Art. no.: 0114.250.30.0 Size: 111 x 52 x 22mm This driver can only be placed externally
	DALI 250mA 6-13W Art. no.: 0114.250.40.1 Size: 97,2 x 43 x 30mm
POWER CABLE OPTIONS Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
	Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0



INFORMATION

Always select a driver option and add the selected driver to your order.

 Full warranty only applies when fixture is purchased in combination with recommended driver.

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
4981.250.30.Δ	CLU701	Citizen	770lm	7,5W	102lm/W	2700K	>90	35.000 Hrs	250mA
4981.300.30.Δ	CLU701	Citizen	828lm	7,5W	110lm/W	3000K	>90	35.000 Hrs	250mA

Δ See colors