



<b>PRODUCT MATERIAL</b>	Steel and aluminium
<b>LIGHT SOURCE</b>	Osram Oslon 3030
<b>MODULE LIFETIME</b>	Approx. 30.000 hours
<b>DRIVER</b>	Including phase cut dimmable driver
<b>COLORS (Δ)</b>	<ul style="list-style-type: none"> <li>○ 3 = RAL 9003 white</li> <li>● 5 = RAL 9005 black</li> <li>● 8 = Anodic brown</li> <li>● 7 = RAL 7043 Anthracite</li> </ul>
<b>BEAM ANGLE</b>	
<b>SIZE</b>	176 X 70mm



**OPTIONS**

<b>ON/OFF SWITCH</b>	Art. no.: 6035.000.00.0
<b>DRIVER OPTIONS</b>	<b>1/10V</b> 350mA 0-6W Art. no.: 0106.350.30.0
	<b>DALI</b> 350mA 3-18W Art. no.: 0118.350.40.2


Designed by  
**remy  
meijers**

**INFORMATION**

The hole for wall mounting should not be any bigger than 60 x 130mm

Full warranty only applies when fixture is purchased in combination with recommended driver.

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



**INSERTS**

White                      White                      Anthracite                      Anodic brown

ARTICLE NUMBER	COLOR	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
6035.300.30.3	○ white	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.35	○● white / black	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.38	○● white / anodic	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.37	○● white / anthra	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.53	●○ black	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.5	● black	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.58	●● black / anodic	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.57	●● black / anthra	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.83	●○ anodic / white	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.85	●● anodic / black	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.8	● anodic	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.87	●● anodic/ anthra	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	350mA
6035.300.30.73	●○ anthra / white	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.75	●● anthra / black	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.78	●● anthra / anodic	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA
6035.300.30.7	● anthra	Oslon 3030	Osram	2 X 150lm	2 X 2,1W	72lm/W	2700K	>90	30.000 Hrs	500mA