



PRODUCT MATERIAL	Steel and aluminium
LIGHT SOURCE	Philips LED module
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including on/off driver
COLORS (Δ)	<ul style="list-style-type: none"> ○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu
REFLECTOR	Aluminium white
ADJUSTABLE	No
SIZE	Different sizes available



OPTIONS

COLORS	Available in all RAL colours on request Additional price + 10%
DIMMABLE	Dali dimmable
SUPENSION SET	1500mm suspension set included
DIFFUSER	White opalic diffuser or Microprismatic UGR<19 option
COLOUR RENDERING INDEX	>80 in standard, other on request
MOVEMENT SENSOR	On request
DAYLIGHT CONTROL SENSOR	On request
TUNABLE WHITE	On request
CYAN ENHANCED STATIC	On request
WIRELESS DIMMABLE	Masterconnect, Easy Air/Zigbee




INFORMATION

Nominal lifetime L90/B10 @60.000 h / 25°C

! The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.

DIFFUSER



ORBIT FLAT 40

ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
OPAL						
Δ See colors						
66.00600.83.E.OP.Δ	Ø430mm	2900lm	17W	170lm/W	3000K	>80
66.00600.81.E.OP.Δ	Ø430mm	2900lm	17W	170lm/W	3500K	>80
66.00600.84.E.OP.Δ	Ø430mm	2900lm	17W	170lm/W	4000K	>80

UGR>19

66.00600.83.E.MPH.Δ	Ø430mm	2900lm	17W	170lm/W	3000K	>80
66.00600.81.E.MPH.Δ	Ø430mm	2900lm	17W	170lm/W	3500K	>80
66.00600.84.E.MPH.Δ	Ø430mm	2900lm	17W	170lm/W	4000K	>80

ORBIT FLAT 80

ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
OPAL						
Δ See colors						
66.00610.83.E.OP.Δ	Ø800mm	8000lm	47W	170lm/W	3000K	>80
66.00610.81.E.OP.Δ	Ø800mm	8000lm	47W	170lm/W	3500K	>80
66.00610.84.E.OP.Δ	Ø800mm	8000lm	47W	170lm/W	4000K	>80

UGR>19

66.00610.83.E.MPH.Δ	Ø800mm	8000lm	47W	170lm/W	3000K	>80
66.00610.81.E.MPH.Δ	Ø800mm	8000lm	47W	170lm/W	3500K	>80
66.00610.84.E.MPH.Δ	Ø800mm	8000lm	47W	170lm/W	4000K	>80