

PRODUCT MATERIAL	Steel and aluminium
LIGHT SOURCE	Philips Ledline
MODULE LIFETIME	Approx. 50.000 hours
DRIVER LEDLINE	Including DALI 2.0 driver
COLORS (Δ)	<ul style="list-style-type: none"> ○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu
DIFFUSER	Opalic white
ADJUSTABLE	No
SIZE	Different sizes available




SPECIAL FEATURES

Luminaire is equipped with EasyAir Sensor:
 Communication between luminaires without wire.
 Easy smartphone commissioning
 Daylight control sensor: EasyAir sensor included
 Movement sensor: EasyAir sensor included
 Dimmable: DALI 2.0 driver included
 Enables gateway data readout
 Xitanium SR interface (based on DALI 2.0)

OPTIONS

COLORS	Available in all RAL colours on request Additional price + 10%
DIFFUSER	White opalic diffuser or Microprismatic UGR<19 option
EMERGENCY	3 hours
SUSPENSION SET	Suspension set 1500mm
IP CLASS	IP20 in standard, IP44 on request
COLOUR RENDERING INDEX	>80 in standard, other on request
MOVEMENT SENSOR	EasyAir sensor included
DAYLIGHT CONTROL SENSOR	EasyAir sensor included
TUNABLE WHITE	On request
CYAN ENHANCED STATIC	On request

DIFFUSER



INFORMATION


Nominal lifetime L90/B10 @60.000 h / 25°C



Bespoke size & product features available




The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
OPAL						
Δ See colors						
66.01100.83.XC.OP.Δ	Ø425mm	5500lm	35W	157lm/W	3000K	>80
66.01100.81.XC.OP.Δ	Ø425mm	5500lm	35W	157lm/W	3500K	>80
66.01100.84.XC.OP.Δ	Ø425mm	5500lm	35W	157lm/W	4000K	>80


ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
UGR<19						
Δ See colors						
66.01100.83.XC.MP19.Δ	Ø425mm	5500lm	35W	157lm/W	3000K	>80
66.01100.81.XC.MP19.Δ	Ø425mm	5500lm	35W	157lm/W	3500K	>80
66.01100.84.XC.MP19.Δ	Ø425mm	5500lm	35W	157lm/W	4000K	>80

ORBIT 50 SR




ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
OPAL						
Δ See colors						
66.01101.83.XC.OP.Δ	Ø500mm	5500lm	35W	157lm/W	3000K	>80
66.01101.81.XC.OP.Δ	Ø500mm	5500lm	35W	157lm/W	3500K	>80
66.01101.84.XC.OP.Δ	Ø500mm	5500lm	35W	157lm/W	4000K	>80

ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
UGR<19						
Δ See colors						
66.01101.83.XC.MP19.Δ	Ø500mm	5500lm	35W	157lm/W	3000K	>80
66.01101.81.XC.MP19.Δ	Ø500mm	5500lm	35W	157lm/W	3500K	>80
66.01101.84.XC.MP19.Δ	Ø500mm	5500lm	35W	157lm/W	4000K	>80



ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
OPAL						
Δ See colors						
66.01110.83.XC.OP.Δ	Ø650mm	8500lm	57W	149lm/W	3000K	>80
66.01110.81.XC.OP.Δ	Ø650mm	8500lm	57W	149lm/W	3500K	>80
66.01110.84.XC.OP.Δ	Ø650mm	8500lm	57W	149lm/W	4000K	>80



ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
OPAL						
Δ See colors						
66.01120.83.XC.OP.Δ	Ø900mm	12000lm	70W	171lm/W	3000K	>80
66.01120.81.XC.OP.Δ	Ø900mm	12000lm	70W	171lm/W	3500K	>80
66.01120.84.XC.OP.Δ	Ø900mm	12000lm	70W	171lm/W	4000K	>80