

| | |
|-------------------------|--|
| PRODUCT MATERIAL | Aluminium profile |
| LIGHT SOURCE | Philips Ledline |
| MODULE LIFETIME | Approx. 50.000 hours |
| DRIVER LEDLINE | Including on/off driver |
| COLORS (Δ) | <ul style="list-style-type: none"> ○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu |
| DIFFUSER | Parabolic louver |
| ADJUSTABLE | No |
| SIZE | Different sizes available |



OPTIONS

| | |
|--------------------------------|---|
| COLORS | Available in all RAL colours on request Additional price + 10% |
| SUSPENSION SET | 1500mm suspension set |
| DIMMABLE | Dali dimmable |
| EMERGENCY | 3 hours |
| COLOUR RENDERING INDEX | >80 in standard, other on request |
| MOVEMENT SENSOR | On request |
| DAYLIGHT CONTROL SENSOR | On request |
| TUNABLE WHITE | On request |
| CYAN ENHANCED STATIC | On request |
| WIRELESS DIMMABLE | Masterconnect, Easy Air/Zigbee |

INFORMATION


Nominal lifetime L80/B10 @70.000 h / 25°C



Bespoke size & product features available



The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



Technical drawing

PROFILE 450 SKY

| ARTICLE NUMBER | LENGTH | GROSS LUMEN OUTPUT | OUTPUT POWER | MODULE EFFICIENCY | COLOR TEMPERATURE | CRI |
|--------------------------|--------|--------------------|--------------|-------------------|-------------------|-----|
| ASYMETRISCH | | | | | | |
| Δ See colors | | | | | | |
| 55.00366.83.E.LNS AS.Δ | 846mm | 3300lm | 20W | 165lm/W | 3000K | >80 |
| 55.00366.81.E.LNS AS.Δ | 846mm | 3300lm | 20W | 165lm/W | 3500K | >80 |
| 55.00366.84.E.LNS AS.Δ | 846mm | 3300lm | 20W | 165lm/W | 4000K | >80 |
| 55.00366.83.E.LNS AS.Δ | 1126mm | 4400lm | 26W | 169lm/W | 3000K | >80 |
| 55.00321.81.E.LNS AS.Δ | 1126mm | 4400lm | 26W | 169lm/W | 3500K | >80 |
| 55.00321.84.E.LNS AS.Δ | 1126mm | 4400lm | 26W | 169lm/W | 4000K | >80 |
| 55.00322.83.E.LNS AS.Δ | 1406mm | 5500lm | 33W | 167lm/W | 3000K | >80 |
| 55.00322.81.E.LNS AS.Δ | 1406mm | 5500lm | 33W | 167lm/W | 3500K | >80 |
| 55.00322.84.E.LNS AS.Δ | 1406mm | 5500lm | 33W | 167lm/W | 4000K | >80 |
| 50° | | | | | | |
| 55.00366.83.E.LNS 50.Δ | 846mm | 3300lm | 20W | 165lm/W | 3000K | >80 |
| 55.00366.81.E.LNS 50.Δ | 846mm | 3300lm | 20W | 165lm/W | 3500K | >80 |
| 55.00366.84.E.LNS 50.Δ | 846mm | 3300lm | 20W | 165lm/W | 4000K | >80 |
| 55.00321.83.E.LNS 50.Δ | 1126mm | 4400lm | 26W | 169lm/W | 3000K | >80 |
| 55.00321.81.E.LNS 50.Δ | 1126mm | 4400lm | 26W | 169lm/W | 3500K | >80 |
| 55.00321.84.E.LNS 50.Δ | 1126mm | 4400lm | 26W | 169lm/W | 4000K | >80 |
| 55.00322.83.E.LNS 50.Δ | 1406mm | 5500lm | 33W | 167lm/W | 3000K | >80 |
| 55.00322.81.E.LNS 50.Δ | 1406mm | 5500lm | 33W | 167lm/W | 3500K | >80 |
| 55.00322.84.E.LNS 50.Δ | 1406mm | 5500lm | 33W | 167lm/W | 4000K | >80 |
| 80° | | | | | | |
| 55.00366.83.E.LNS 80.Δ | 846mm | 3300lm | 20W | 165lm/W | 3000K | >80 |
| 55.00366.81.E.LNS 80.Δ | 846mm | 3300lm | 20W | 165lm/W | 3500K | >80 |
| 55.00366.84.E.LNS 80.Δ | 846mm | 3300lm | 20W | 165lm/W | 4000K | >80 |
| 55.00321.83.E.LNS 80.Δ | 1126mm | 4400lm | 26W | 169lm/W | 3000K | >80 |
| 55.00321.81.E.LNS 80.Δ | 1126mm | 4400lm | 26W | 169lm/W | 3500K | >80 |
| 55.00321.84.E.LNS 80.Δ | 1126mm | 4400lm | 26W | 169lm/W | 4000K | >80 |
| 55.00322.83.E.LNS 80.Δ | 1406mm | 5500lm | 33W | 167lm/W | 3000K | >80 |
| 55.00322.81.E.LNS 80.Δ | 1406mm | 5500lm | 33W | 167lm/W | 3500K | >80 |
| 55.00322.84.E.LNS 80.Δ | 1406mm | 5500lm | 33W | 167lm/W | 4000K | >80 |
| UP/DN ASYMETRISCH | | | | | | |
| 55.00325.83.E.LNS AS.Δ | 846mm | 5500lm | 33W | 167lm/W | 3000K | >80 |
| 55.00325.81.E.LNS AS.Δ | 846mm | 5500lm | 33W | 167lm/W | 3500K | >80 |
| 55.00325.84.E.LNS AS.Δ | 846mm | 5500lm | 33W | 167lm/W | 4000K | >80 |
| 55.00326.83.E.LNS AS.Δ | 1126mm | 7700lm | 46W | 167lm/W | 3000K | >80 |
| 55.00326.81.E.LNS AS.Δ | 1126mm | 7700lm | 46W | 167lm/W | 3500K | >80 |
| 55.00326.84.E.LNS AS.Δ | 1126mm | 7700lm | 46W | 167lm/W | 4000K | >80 |
| 55.00327.83.E.LNS AS.Δ | 1406mm | 9900lm | 58W | 171lm/W | 3000K | >80 |
| 55.00327.81.E.LNS AS.Δ | 1406mm | 9900lm | 58W | 171lm/W | 3500K | >80 |
| 55.00327.84.E.LNS AS.Δ | 1406mm | 9900lm | 58W | 171lm/W | 4000K | >80 |
| UP/DN 50° | | | | | | |
| 55.00325.83.E.LNS 50.Δ | 846mm | 5500lm | 33W | 167lm/W | 3000K | >80 |
| 55.00325.81.E.LNS 50.Δ | 846mm | 5500lm | 33W | 167lm/W | 3500K | >80 |
| 55.00325.84.E.LNS 50.Δ | 846mm | 5500lm | 33W | 167lm/W | 4000K | >80 |
| 55.00326.83.E.LNS 50.Δ | 1126mm | 7700lm | 46W | 167lm/W | 3000K | >80 |
| 55.00326.81.E.LNS 50.Δ | 1126mm | 7700lm | 46W | 167lm/W | 3500K | >80 |
| 55.00326.84.E.LNS 50.Δ | 1126mm | 7700lm | 46W | 167lm/W | 4000K | >80 |
| 55.00327.83.E.LNS 50.Δ | 1406mm | 9900lm | 58W | 171lm/W | 3000K | >80 |
| 55.00327.81.E.LNS 50.Δ | 1406mm | 9900lm | 58W | 171lm/W | 3500K | >80 |
| 55.00327.84.E.LNS 50.Δ | 1406mm | 9900lm | 58W | 171lm/W | 4000K | >80 |
| UP/DN 80° | | | | | | |
| 55.00325.83.E.LNS 80.Δ | 846mm | 5500lm | 33W | 167lm/W | 3000K | >80 |
| 55.00325.81.E.LNS 80.Δ | 846mm | 5500lm | 33W | 167lm/W | 3500K | >80 |
| 55.00325.84.E.LNS 80.Δ | 846mm | 5500lm | 33W | 167lm/W | 4000K | >80 |
| 55.00326.83.E.LNS 80.Δ | 1126mm | 7700lm | 46W | 167lm/W | 3000K | >80 |
| 55.00326.81.E.LNS 80.Δ | 1126mm | 7700lm | 46W | 167lm/W | 3500K | >80 |
| 55.00326.84.E.LNS 80.Δ | 1126mm | 7700lm | 46W | 167lm/W | 4000K | >80 |
| 55.00327.83.E.LNS 80.Δ | 1406mm | 9900lm | 58W | 171lm/W | 3000K | >80 |
| 55.00327.81.E.LNS 80.Δ | 1406mm | 9900lm | 58W | 171lm/W | 3500K | >80 |
| 55.00327.84.E.LNS 80.Δ | 1406mm | 9900lm | 58W | 171lm/W | 4000K | >80 |