


PRODUCT MATERIAL	Aluminium profile
LIGHT SOURCE	Philips Ledline
MODULE LIFETIME	Approx. 50.000 hours
DRIVER LEDLINE	Including driver
COLORS (Δ)	<ul style="list-style-type: none"> ○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu
REFLECTOR	Aluminium white
ADJUSTABLE	No
SIZE	See technical drawing



OPTIONS

COLORS	Available in all RAL colours on request Additional price + 10%
DIMMABLE	Dali dimmable
SUSPENSION SET	1500mm suspension set included
DIFFUSER	White opalic diffuser or Microprismatic UGR<19 option
EMERGENCY	3 hours
IP CLASS	IP20 in standard, IP44 on request
COLOUR RENDERING INDEX	>80 in standard, other on request
MOVEMENT SENSOR	On request
DAYLIGHT CONTROL SENSOR	On request
TUNABLE WHITE	On request
CYAN ENHANCED STATIC	On request
WIRELESS DIMMABLE	Masterconnect, Easy Air/Zigbee



Technical drawing

DIFFUSER



White opalic



Microprismatic
UGR<19

INFORMATION

Nominal lifetime 70.000/L80B10

Bespoke size & product features available

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.

ARTICLE NUMBER	LENGTH	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
Opal						
Δ See colors						
55.00450.83.E.OP.Δ	960mm	9900lm	58W	171lm/W	3000K	>80
55.00450.81.E.OP.Δ	960mm	9900lm	58W	171lm/W	3500K	>80
55.00450.84.E.OP.Δ	960mm	9900lm	58W	171lm/W	4000K	>80
55.00451.83.E.OP.Δ	1240mm	13200lm	78W	169lm/W	3000K	>80
55.00451.81.E.OP.Δ	1240mm	13200lm	78W	169lm/W	3500K	>80
55.00451.84.E.OP.Δ	1240mm	13200lm	78W	169lm/W	4000K	>80
55.00452.83.E.OP.Δ	1550mm	16500lm	99W	167lm/W	3000K	>80
55.00452.81.E.OP.Δ	1550mm	16500lm	99W	167lm/W	3500K	>80
55.00452.84.E.OP.Δ	1550mm	16500lm	99W	167lm/W	4000K	>80
UGR<19						
55.00450.83.E.MP19.Δ	960mm	9900lm	58W	171lm/W	3000K	>80
55.00450.81.E.MP19.Δ	960mm	9900lm	58W	171lm/W	3500K	>80
55.00450.84.E.MP19.Δ	960mm	9900lm	58W	171lm/W	4000K	>80
55.00451.83.E.MP19.Δ	1240mm	13200lm	78W	169lm/W	3000K	>80
55.00451.81.E.MP19.Δ	1240mm	13200lm	78W	169lm/W	3500K	>80
55.00451.84.E.MP19.Δ	1240mm	13200lm	78W	169lm/W	4000K	>80
55.00452.83.E.MP19.Δ	1550mm	16500lm	99W	167lm/W	3000K	>80
55.00452.81.E.MP19.Δ	1550mm	16500lm	99W	167lm/W	3500K	>80
55.00452.84.E.MP19.Δ	1550mm	16500lm	99W	167lm/W	4000K	>80