

PRODUCT MATERIAL	Aluminium
LIGHT SOURCE	LMR50
MODULE LIFETIME	Approx. 30.000 hours
DRIVER	Excluding driver, SELECT OPTION
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
BEAM ANGLE	▲ 20° ▲ 30°
ADJUSTABLE	Yes
SIZE	200 X 100 X 90mm



OPTIONS LMR50


GLASS COVER CLEAR	Glass IP44	Art. no.: 2X0053.999.99.0
DRIVER OPTIONS	On/off	350mA 11-16W Art. no.: 0116.350.10.3
	Phase cut	350mA 5-10W Art. no.: 2X0110.350.30.1
	DALI	350mA 3-18W Art. no.: 0118.350.40.0
POWER CABLE OPTIONS Connected to driver/fixture	Europlug 2000mm 2X0,75 Art. no.: 2X0502.075.20.0	
	Wieland GST18/3 male 2000mm 3X0,75 Art. no.: 2X0501.183.20.0	
	Wieland T connector GST18/3 200mm 3X0,75 Art. no.: 2X0500.183.20.0	

INFORMATION


Always select a driver option and add the selected driver to your order.



Full warranty only applies when fixture is purchased in combination with recommended driver.



Hole size



Technical drawing

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	BEAM ANGLE	mA
Δ See colors										
4907.171.20.Δ	LMR50	Bridgelux V6	2 X 575lm	2 X 6,8W	85lm/W	2700K	>90	30.000 Hrs	20°	350mA
4907.172.30.Δ	LMR50	Bridgelux V6	2 X 575lm	2 X 6,8W	85lm/W	2700K	>90	30.000 Hrs	30°	350mA
4907.173.20.Δ	LMR50	Bridgelux V6	2 X 600lm	2 X 6,8W	88lm/W	3000K	>90	30.000 Hrs	20°	350mA
4907.174.30.Δ	LMR50	Bridgelux V6	2 X 600lm	2 X 6,8W	88lm/W	3000K	>90	30.000 Hrs	30°	350mA
4907.275.20.Δ	LMR50	Bridgelux DtW	2 X 535lm	2 X 7W	77lm/W	1800-3000K	DTW 95	30.000 Hrs	20°	350mA
4907.276.30.Δ	LMR50	Bridgelux DtW	2 X 535lm	2 X 7W	77lm/W	1800-3000K	DTW 95	30.000 Hrs	30°	350mA