




PRODUCT MATERIAL	Aluminium
LIGHT SOURCE	LED GU10
MODULE LIFETIME	Approx. 30.000 / 50.000 hours
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu
BEAM ANGLE	 25°  36°
BEAM ANGLE (DTW)	 30°
ADJUSTABLE	350°
ADJUSTABLE HEAD	90°
SIZE	See technical drawing




OPTIONS

ANTI-GLARE RING	Black anti-glare ring	Included
	Gold anti-glare ring	Art. no.: 4 X 5033.922.99.9

INFORMATION

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.




Technical drawing

ANTI-GLARE RING



Black Gold

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	BEAM ANGLE
Δ See colors									
5035.272.25.Δ	GU10	Philips	4 X 265lm	4 X 4W	66lm/W	2700K	>90	50.000 Hrs	25°
5035.279.36.Δ	GU10	Philips	4 X 265lm	4 X 4W	66lm/W	2700K	>90	50.000 Hrs	36°
5035.282.25.Δ	GU10	Philips	4 X 280lm	4 X 4W	70lm/W	3000K	>90	50.000 Hrs	25°
5035.290.36.Δ	GU10	Philips	4 X 280lm	4 X 4W	70lm/W	3000K	>90	50.000 Hrs	36°
5035.176.30.Δ	GU10	KL	4 X 305lm	4 X 5W	61lm/W	2000 - 3000K	 >90	30.000 Hrs	30°