

PRODUCT MATERIAL	Steel and aluminium
LIGHT SOURCE	Philips LED Module
MODULE LIFETIME	Approx. 30.000 hours
DRIVER	Including on/off driver
COLORS (Δ)	<ul style="list-style-type: none"> ○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu
BEAM ANGLE	<ul style="list-style-type: none"> ▲ 10° ▲ 25° ▲ 35° ▲ 55°
ADJUSTABLE	No
SIZE	∅90 X 360mm




OPTIONS

COLORS	Available in all RAL colours on request Additional price + 10%
DIMMABLE	DALI dimmable

INFORMATION

Nominal lifetime L80/B10 @50.000 h / 25°C

! The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



ARTICLE NUMBER	OPTICS	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
Δ See colors						
55.00250.83.E.10.LNS.CG.Δ	10°	1400lm	12W	116lm/W	3000K	>80
55.00250.81.E.10.LNS.CG.Δ	10°	1400lm	12W	116lm/W	3500K	>80
55.00250.84.E.10.LNS.CG.Δ	10°	1400lm	12W	116lm/W	4000K	>80
55.00250.83.E.25.LNS.CG.Δ	25°	1400lm	12W	116lm/W	3000K	>80
55.00250.81.E.25.LNS.CG.Δ	25°	1400lm	12W	116lm/W	3500K	>80
55.00250.84.E.25.LNS.CG.Δ	25°	1400lm	12W	116lm/W	4000K	>80
55.00250.83.E.35.LNS.CG.Δ	35°	1400lm	12W	116lm/W	3000K	>80
55.00250.81.E.35.LNS.CG.Δ	35°	1400lm	12W	116lm/W	3500K	>80
55.00250.84.E.35.LNS.CG.Δ	35°	1400lm	12W	157m/W	4000K	>80
55.00250.83.E.55.LNS.CG.Δ	55°	1400lm	12W	116lm/W	3000K	>80
55.00250.81.E.55.LNS.CG.Δ	55°	1400lm	12W	116lm/W	3500K	>80
55.00250.84.E.55.LNS.CG.Δ	55°	1400lm	12W	116lm/W	4000K	>80