



# VENUS DUO

<b>PRODUCT MATERIAL</b>	Die-cast aluminium
<b>LIGHT SOURCE</b>	Bridgelux DtW
<b>MODULE LIFETIME</b>	Approx. 50.000 hours
<b>DRIVER</b>	Including phase cut dimmable driver
<b>COLORS (Δ)</b>	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
<b>BEAM ANGLE</b>	▲ 24°
<b>ADJUSTABLE</b>	Rotating 350°, 55° tiltable
<b>DIMMABLE</b>	Yes
<b>SIZE</b>	Ø59 X 292 X 36mm



## OPTIONS


<b>OPTIONAL BEAM ANGLE</b>	▲ 36° Art. no.: 2 X 3066.010.36.0
	▲ 50° Art. no.: 2 X 3066.010.50.0
<b>ANTI-GLARE RING</b>	Black anti-glare ring Included
	Gold mat anti-glare ring Art. no.: 2 X 3066.030.00.9
<b>HONEYCOMB</b>	Art. no.: 2 X 3066.040.00.0
<b>DRIVER OPTIONS</b>	<b>DALI</b> 500mA 12-20W Art. no.: 0120.500.40.2

## INFORMATION

Also available in track and recessed version

Full warranty only applies when fixture is purchased in combination with recommended driver.

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



### ANTI-GLARE RING



### HONEYCOMB



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
5068.125.24.Δ	DtW	Bridgelux	2 X 900lm	2 X 10W	90lm/W	1800-3000K <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">DtW</span>	>90	50.000 Hrs	500mA

Δ See colors