







<b>PRODUCT MATERIAL</b>	Die-cast aluminium
<b>LIGHT SOURCE</b>	Bridgelux DtW
<b>MODULE LIFETIME</b>	Approx. 50.000 hours
<b>DRIVER</b>	Including phase cut dimmable driver
<b>COLORS (Δ)</b>	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
<b>BEAM ANGLE</b>	 24°
<b>ADJUSTABLE</b>	Rotating 350°, 55° tiltable
<b>DIMMABLE</b>	Yes
<b>SIZE</b>	Ø59 X 62mm



## OPTIONS

<b>OPTIONAL BEAM ANGLE</b>	 36°	Art. no.: 3066.010.36.0
	 50°	Art. no.: 3066.010.50.0
<b>ANTI-GLARE RING</b>	<b>Black</b>	Included
	<b>Gold</b>	Art. no.: 3066.030.00.9
<b>HONEYCOMB</b>	Art. no.: 3066.040.00.0	
<b>DRIVER OPTIONS</b>	<b>1/10V</b>	250mA1-14W Art. no.: 0114.250.30.0 Size: 111 x 52 x 22mm
	<b>DALI</b>	250mA 6-13W Art. no.: 0114.250.40.1 Size: 97,2 x 43 x 30mm
<b>POWER CABLE OPTIONS</b> Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0	
	Wieland GST18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0	
	Wieland T connector GST18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0	


 Design Patent Certificate  
No: ZL 2019 3 0427879.1 Recessed Mount Venus Patent



## INFORMATION


 Full warranty only applies when fixture is purchased in combination with recommended driver.

### ANTI-GLARE RING



### HONEYCOMB



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
4066.125.24.Δ	DtW	Bridgelux	900lm	10W	90lm/W	1800-3000K  >90	>90	50.000 Hrs	250mA

Δ See colors

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.