KEYLIGHT

PRODUCT MATERIAL

LIGHT SOURCE MODULE LIFETIME

DRIVER

COLORS (Δ)

ADJUSTABLE

OPTIONS

COLORS

DIMMABLE

DIFFUSER

UGR DIFFUSER

MOVEMENT SENSOR

INFORMATION

IP CLASS

SIZE

IP20 ∰ C€

Steel and aluminium Philips LED module

Approx. 50.000 hours

3 = RAL 9003 white 5 = RAL 9005 black

6 = RAL 9006 alu

Additional price + 10%

Microprismatic in standard White acrilic diffuser, acrilic frosted or any other on request

IP20 in standard, IP44 on request

DALI dimmable

UGR<19 diffuser

On request

On request

Available in all RAL colours on request

On request

On request

2008 X 640mm


Including driver


No





OFFICE PILE S







White acrilic

Microprismati

ART.NR. ∆ see colors	LAMP TYPE	BRAND	LIGHT OUTPUT	MODULE POWER	MODULE EFFICIENCY	CORRELATED COLOUR TEMPERATURE	COLOUR RENDERING INDEX	TC LIFE
9900.000.30.Δ	LED module	Philips	4400lm	29W	152lm/W	3000K	>80	50.000 Hrs
9900.000.40.Δ	LED module	Philips	4400lm	29W	152lm/W	4000K	>80	50.000 Hrs
UP/DN								
9901.000.30.Δ	LED module	Philips	8800lm	57W	154lm/W	3000K	>80	50.000 Hrs
9901.000.40.∆	LED module	Philips	8800lm	57W	154lm/W	4000K	>80	50.000 Hrs

DAYLIGHT CONTROL SENSOR

Mounting: Free standing Available in up/dn version

Keylight International reserves the right to modify or change technical, contruction or LED specifications due to continuous improvements of our products and lightsources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.

5 Years