











PRODUCT MATERIAL LIGHT SOURCE MODULE LIFETIME DRIVER

Steel and aluminium Philips LED module Approx. 50.000 hours Including driver

○ **3** = RAL 9003 white 5 = RAL 9005 black **6** = RAL 9006 alu

ADJUSTABLE No

SIZE 2008 X 638mm

## **OPTIONS**

COLORS ( $\Delta$ )

COLORS Available in all RAL colours on request Additional price + 10% **EMERGENCY BALLAST** 0187.003.01.0 - 1 hour DIMMABLE DALI dimmable DIFFUSER Microprismatic in standard White acrilic diffuser, acrilic frosted or any other on request UGR<19 diffuser on request **UGR DIFFUSER** IP CLASS IP20 in standard, IP44 on request MOVEMENT SENSOR On request

## INFORMATION

WARRANTY	5 Vears	

On request

## Mounting: Free standing


DAYLIGHT CONTROL SENSOR

Available in up/dn version

Key light International reserves the right to modify or change technical, contruction or LED specifications due to continuous improvements of our products and light sources. The light source in this product can be replaced with an equivalent module made by Phillips, Osram or Tridonic.



OFFICE PILE









White acrilic

Acrilic frosted

Microprismatic

ART.NR.	LAMP TYPE	BRAND	LIGHT OUTPUT	MODULE POWER	MODULE EFFICIENCY	CORRELATED COLOUR TEMPERATURE	COLOUR RENDERING INDEX	TCLIFE
Δ see colors								
9902.000.30.Δ	LED module	Philips	5200lm	35W	152lm/W	3000K	>80	50.000 Hrs
9902.000.40.Δ	LED module	Philips	5200lm	35W	152lm/W	4000K	>80	50.000 Hrs
UP/DN								
9903.000.30.Δ	LED module	Philips	10400lm	70W	154lm/W	3000K	>80	50.000 Hrs
9903.000.40.Δ	LED module	Philips	10400lm	70W	154lm/W	4000K	>80	50.000 Hrs